

✓ Round / flat framed "Low Profile Bonnell" Unit



Technical specifications:

- Number of turns: 4
- Height of the spring: from 8 mm. to 115 mm.
- Diameter of the cup: from 80 mm. to 90 mm.
- Thickness of wire: Ø 2.10 mm.; Ø 2.20 mm.; Ø 2.30 mm.; Ø 2.40 mm.
(From 14 g. to 12 3/4 g.)
- Helical wire: Ø 1.35 mm. (17 g.)
- Round frame wire: Ø 4.50 mm. (7 g.)
- Oil tempered steel flat wire frame: 10 x 1.7 mm.

| Mattress Size | Units Size | Width | | | | |
|---------------|------------|--------|--------|---------|---------|---------|
| | | 90 | 105 | 135 | 140 | 150 |
| | | 87 | 102 | 132 | 137 | 147 |
| 182 | 179 | 8 X 21 | 9 X 21 | 12 X 21 | 12 X 21 | 14 X 21 |
| 190 | 187 | 8 X 22 | 9 X 22 | 12 X 22 | 12 X 22 | 14 X 22 |
| 200 | 196 | 8 X 23 | 9 X 23 | 12 X 23 | 12 X 23 | 14 X 23 |

Press packed in 14/20 units (metal or timber grids)

Roll packed in 14 units/roll (Kraft paper)